



PRIME ELASTOMERIC PAINT

TECHNICAL DATA SHEET



PRODUCT DESCRIPTION

PRIME ELASTOMERIC PAINT provides an excellent waterproofing property, forming a seamless and durable barrier against water infiltration. This is specially formulated to be flexible, allowing them to stretch and move with the substrate without cracking or delamination.



RECOMMENDED APPLICATIONS

For concrete waterproofing which requires weather resistance, protecting the underlying surface from damage caused by prolonged exposure to rain and sunlight.



ADVANTAGES

- Breathable, allowing moisture vapor to escape from the substrate while preventing water penetration
- Easy to apply
- Good adhesion to various substrates such as concrete,



PRODUCT INFORMATION

COLOR: Grey, red and white

POT LIFE: Greater than 15 hours at 25 degrees Celsius.

PACKAGING: 1 gallon/16L pail

STORAGE: Store in a cool, dry place, away from direct sunlight.

SHELF LIFE: 12 months from manufacturing date



ENVIRONMENT

Our facility complies with the proper waste management procedures. Our products are also free of ozone depleting substances.



COVERAGE

20-24 sqm per gal depending on the method of application, the thickness of deposit and the texture and porosity of the substrate.



SUSTAINABILITY

Our company is committed to Carbon Neutrality thru our various programs such as our GHG Emission Reduction Logistics Approach and OPTI Trees Planting Program.



APPLICATION INSTRUCTION

Surface Preparation: Ensure that the surface is clean, dry, and free from dust, grease, oil, loose paint, or any other contaminants. Use a wire brush, scraper, or pressure washer if necessary to remove loose or peeling paint. Repair any cracks, holes, or damaged areas on the surface.

Mixing: Thoroughly stir the elastomeric paint to achieve a consistent and homogenous mixture.

Application: Use a high-quality brush, roller, or sprayer to apply the elastomeric paint. Start from the top and work your way down. Apply the paint in smooth, even strokes, ensuring proper coverage.

Layering: Depending on the specific product and desired results, you may need to apply multiple coats of elastomeric paint. Allow each coat to dry completely before applying the next one.

Drying and Curing: Give the final coat of elastomeric paint 3 hrs to dry



QUALITY & DURABILITY ASSURANCE

Our stringent Quality Assurance Procedure for every batch of products manufactured. Our R&D Laboratory based in our production facility ensures that scientific Quality Control Parameters are measured for quality.

Our Quality Control Parameters ensure the stability of our products, ensuring the long-term durability amid exposure to various element and weather conditions.

COLORZONE VENTURES CORPORATION

ADDRESS: BLK 1 LOT 6 KIANA BLDG, SOLUNA COMMERCIAL BACOR BLVD.CITY OF BACOR CAVITE

EMAIL: colorzoneph@gmail.com

CONTACT NO: +6346 238 2133 / +63 917 817 3960